REVISIONS				
REV	DESCRIPTION	CHECK	APPROVAL	DATE



DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	SIZE	TOLERANCE	PLATED	QTY
A	9.8	+3.0/-3.0	PLATED	3
B	13.0	+3.0/-3.0	PLATED	33
C	31.5	+3.0/-3.0	PLATED	8
D	39.4	+3.0/-3.0	PLATED	10
E	40.2	+3.0/-3.0	PLATED	17

REFERENCE LAYER STACKUP (Unitsmils)

Purchase Order & Specification Sheet			
Board Name : DCDC_AUX_BOARD		Board Thickness : 1.60mm +/- 10%	Layers : 4
Dielectric Material : FR4		Spell Mode : 1 X 1	Board Cut Out : Yes
Surface Finished :	Lead Free HAL		Tin Thickness: 1-40um
Soldermask Colors :	Green	E-TEST Checker : Yes	
Silk Screen Colors :	White	UL-MAKE : Yes	UL-MAKE Layer : Silk Top
Outline Profile :	Router	Gold Finger Plating:No	

Fab Notes:
1. Fabricate to IPC-6012-II, current revision.
2. All vias need to be plugged.
3. Attention: the thickness of the material's adjustment should be less than 20% for each layer(Core/PP).
   For instance: the thickness of Core-1 is 4mil, then the adjustment range will be 3.2-4.8mil.

hampoo	Shenzhen Hampoo Science&Technology Co.,Ltd .		
	FABRICATIN DETAIL 1: 2: 3:	SIZE: A1	REV:
			SHEET:1OF1
E-MAIL: support@hampoo.com	BUSHMASTER:	DATE:	
TEL : 086-0755-86185500	PART NO.		
FAX : 086-0755-86185505	WEBSITE: WWW.HAMPOO.COM	SCALE: 1/1	