



CPM3-3300-R050A

Wolfspeed SiC Gen3 MOSFET

Description

This is Wolfspeed's 3rd generation high-performance silicon carbide MOSFET in a package-less bare die format to be implemented into any custom module design.



G - Gate
S - Source
D - Drain

Package Type: Bare Die
PN: CPM3-3300-R050A

Features

- Enhanced 3rd Generation SiC MOSFET
- High blocking voltage with low on-resistance
- Easy to parallel and simple to drive
- Temperature-independent high-speed switching
- Integrated lumped gate resistance

Typical Applications

- Medium-voltage motor drives
- Renewable energy
- Smart grid/grid-tie power generation
- Pulsed-power applications
- Rail traction

Absolute Maximum Ratings

Stress beyond those listed under absolute maximum ratings may damage the device.

Parameter	Symbol	Rating	Unit
Drain-Source Voltage, across T_{VJ}	$V_{DS(max)}$	3300	V
Maximum Gate-Source Voltage, Peak Transient Capability	$V_{GS(max)}$	-10/+20	V
Continuous Drain Current, $V_{GS} = 15$ V, assumes die packaged with typical $R_{th(j-c)} = 0.41$ K/W	I_{DS}	$T_c = 25$ °C	52
		$T_c = 100$ °C	36
Pulsed Drain Current, t_p limited by $T_{VJ(max)}$	$I_{DS(pulse)}$	104	A
Virtual Junction and Storage Temperature	T_{VJ}, T_{stg}	-55 to +175	°C
Maximum Processing Temperature, in non-reactive ambient	T_{proc}	325	°C

Recommended Operating Conditions

Parameter	Symbol	Rating	Unit
Recommended Operating Gate-Source Voltage	$V_{GS(op)}$	-5/+15	V



Electrical Characteristics ($T_{VJ} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	3300			V	$V_{GS} = 0\text{ V}, I_{DS} = 100\text{ }\mu\text{A}$
Gate Threshold Voltage	$V_{GS(th)}$	2.6	3.5	4.4	V	$V_{DS} = V_{GS}, I_{DS} = 26.5\text{ mA}$
			2.6		V	$V_{DS} = V_{GS}, I_{DS} = 26.5\text{ mA}, T_{VJ} = 175\text{ }^{\circ}\text{C}$
Zero Gate Voltage Drain Current	I_{DSS}		5	30	μA	$V_{DS} = 3300\text{ V}, V_{GS} = 0\text{ V}$
Gate-Source Leakage Current	I_{GSS}		10	250	nA	$V_{GS} = 15\text{ V}, V_{DS} = 0\text{ V}$
Drain-Source On-State Resistance	$R_{DS(on)}$		53	69	m Ω	$V_{GS} = 15\text{ V}, I_{DS} = 40\text{ A}$
			136			$V_{GS} = 15\text{ V}, I_{DS} = 40\text{ A}, T_{VJ} = 175\text{ }^{\circ}\text{C}$
Transconductance	g_{fs}		26		S	$V_{DS} = 20\text{ V}, I_{DS} = 40\text{ A}$
			27			$V_{DS} = 20\text{ V}, I_{DS} = 40\text{ A}, T_{VJ} = 175\text{ }^{\circ}\text{C}$
Input Capacitance	C_{iss}		7240		pF	$V_{GS} = 0\text{ V}, V_{DS} = 1800\text{ V}$ $f = 100\text{ kHz}$ $V_{AC} = 25\text{ mV}$
Output Capacitance	C_{oss}		100			
Reverse Transfer Capacitance	C_{rss}		6			
C_{oss} Stored Energy	E_{oss}		210		μJ	$V_{DS} = 1800\text{ V}, f = 100\text{ kHz}$
Internal Gate Resistance	$R_{G(int)}$		8.8		Ω	$f = 100\text{ kHz}, V_{AC} = 25\text{ mV}$
Gate to Source Charge	Q_{gs}		131		nC	$V_{DS} = 2000\text{ V}, V_{GS} = -5\text{ V}/+15\text{ V}$ $I_{DS} = 50\text{ A}$
Gate to Drain Charge	Q_{gd}		19			
Total Gate Charge	Q_g		255			

Reverse Diode Characteristics ($T_{VJ} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Diode Forward Voltage	V_{SD}		4.9		V	$V_{GS} = -5\text{ V}, I_{SD} = 20\text{ A}$
			4.1		V	$V_{GS} = -5\text{ V}, I_{SD} = 20\text{ A}, T_{VJ} = 175\text{ }^{\circ}\text{C}$
Reverse Recovery Time	t_{rr}		126		ns	$V_{GS} = -5\text{ V}, I_{SD} = 40\text{ A}, V_R = 1800\text{ V};$ $di_f/dt = 700\text{ A}/\mu\text{s}, T_{VJ} = 175\text{ }^{\circ}\text{C}$
Reverse Recovery Charge	Q_{rr}		2970		nC	
Peak Reverse Recovery Current	I_{rrm}		47		A	



Typical Performance




Figure 1.

Output Characteristics at $T_{VJ} = -55\text{ }^{\circ}\text{C}$




Figure 2.

Output Characteristics at $T_{VJ} = 25\text{ }^{\circ}\text{C}$




Figure 3.

Output Characteristics at $T_{VJ} = 175\text{ }^{\circ}\text{C}$




Figure 4.

Normalized On-Resistance vs. Temperature




Figure 5.

On-Resistance vs. Drain Current for Various Temperatures




Figure 6.

On-Resistance vs. Temperature for Various Gate Voltages



Typical Performance




Figure 7.

Transfer Characteristic for Various Junction Temperatures




Figure 8.

Body Diode Characteristics at $T_{VJ} = -55\text{ }^{\circ}\text{C}$




Figure 9.

Body Diode Characteristics at $T_{VJ} = 25\text{ }^{\circ}\text{C}$




Figure 10.

Body Diode Characteristics at $T_{VJ} = 175\text{ }^{\circ}\text{C}$




Figure 11.

Threshold Voltage vs. Temperature




Figure 12.

Gate Charge Characteristic



Typical Performance




Figure 13.

3rd Quadrant Characteristics at $T_{VJ} = -55\text{ }^{\circ}\text{C}$




Figure 14.

3rd Quadrant Characteristics at $T_{VJ} = 25\text{ }^{\circ}\text{C}$




Figure 15.

3rd Quadrant Characteristics at $T_{VJ} = 175\text{ }^{\circ}\text{C}$




Figure 16.

Output Capacitor Stored Energy




Figure 17.

Capacitances vs. Drain-Source Voltage (0 - 200 V)





Figure 18.

Capacitances vs. Drain-Source Voltage (0 - 3000 V)



Product Dimensions CPM3-3300-R050A

Die Dimensions (mm)



Mechanical Dimensions CPM3-3300-R050A

Parameter	Typical	Unit
Die Size (L × W)	4.90 × 7.70	mm
Exposed Source Pad Metal Dimensions	1.83 × 6.68 (× 2)	mm
Gate Pad Dimensions	0.6 × 1.3	mm
Chip Thickness ¹	400 ± 40	µm
Frontside (Source) Metallization (Al)	4	µm
Frontside (Gate) Metallization (Al)	4	µm
Backside (Drain) Metallization (Ni/Au)	0.8 / 0.1	µm

¹ SiC wafer thickness



Product Ordering Information

Order Number	Description	Package
CPM3-3300-R050A-FS6	3300V/53mΩ SiC MOSFET G3 IND UV DUR	Bare Die Product

Revision History

Revision Number	Date of Change	Brief Summary
1	04/28/2023	Initial Release.
2	09/20/2024	Disclaimers Update

Notes & Disclaimers



WOLFSPEED PROVIDES TECHNICAL AND RELIABILITY DATA, DESIGN RESOURCES, APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, WITH RESPECT THERETO, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

This document and the information contained herein are subject to change without notice. Any such change shall be evidenced by the publication of an updated version of this document by Wolfspeed. No communication from any employee or agent of Wolfspeed or any third party shall effect an amendment or modification of this document. No responsibility is assumed by Wolfspeed for any infringement of patents or other rights of third parties which may result from use of the information contained herein. No license is granted by implication or otherwise under any patent or patent rights of Wolfspeed.

The information contained in this document (excluding examples, as well as figures or values that are labeled as “typical”) constitutes Wolfspeed’s sole published specifications for the subject product. “Typical” parameters are the average values expected by Wolfspeed in large quantities and are provided for informational purposes only. Any examples provided herein have not been produced under conditions intended to replicate any specific end use. Product performance can and does vary due to a number of factors.

This product has not been designed or tested for use in, and is not intended for use in, any application in which failure of the product would reasonably be expected to cause death, personal injury, or property damage. For purposes of (but without limiting) the foregoing, this product is not designed, intended, or authorized for use as a critical component in equipment implanted into the human body, life-support machines, cardiac defibrillators, and similar emergency medical equipment; air traffic control systems; or equipment used in the planning, construction, maintenance, or operation of nuclear facilities. Notwithstanding any application-specific information, guidance, assistance, or support that Wolfspeed may provide, the buyer of this product is solely responsible for determining the suitability of this product for the buyer’s purposes, including without limitation (1) selecting the appropriate Wolfspeed products for the buyer’s application, (2) designing, validating, and testing the buyer’s application, and (3) ensuring the buyer’s application meets applicable standards and any other legal, regulatory, and safety-related requirements.

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Wolfspeed representative or from the Product Documentation sections of www.wolfspeed.com.

REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact your Wolfspeed representative to ensure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

Contact info:

4600 Silicon Drive
Durham, NC 27703 USA
Tel: +1.919.313.5300
www.wolfspeed.com/power