

# C3M0032120J2

Silicon Carbide Power MOSFET  
N-Channel Enhancement Mode

## Features

- 3rd generation SiC MOSFET technology
- Optimized package with separate driver source pin
- Larger drain tab for better thermal performance
- High blocking voltage with low on-resistance
- High-speed switching with low capacitances
- Fast intrinsic diode with low reverse recovery ( $Q_{rr}$ )
- Halogen free, RoHS compliant


## Benefits

- Reduce switching losses and minimize gate ringing
- Higher system efficiency
- Reduce cooling requirements
- Increase power density
- Increase system switching frequency

## Typical Applications

- Motor Control
- EV Battery Chargers
- High Voltage DC/DC Converters

## Package



Part Number	Package	Marking
C3M0032120J2	TO-263-7XL	C3M0032120J2

## Key Parameters

Parameter	Symbol	Min.	Typ.	Max	Unit	Conditions	Note
Drain - Source Voltage	$V_{DS}$			1200	V	$T_c = 25^\circ\text{C}$	
Maximum Gate - Source Voltage	$V_{GS(max)}$	-8		+19		Transient	
Operational Gate-Source Voltage	$V_{GS op}$		-4/15			Static	Note 1
DC Continuous Drain Current	$I_D$			74	A	$V_{GS} = 15\text{ V}, T_c = 25^\circ\text{C}, T_J \leq 175^\circ\text{C}$	Fig. 19
				53		$V_{GS} = 15\text{ V}, T_c = 100^\circ\text{C}, T_J \leq 175^\circ\text{C}$	Note 2
Pulsed Drain Current	$I_{DM}$			264		$t_{Pmax}$ limited by $T_{Jmax}$ $V_{GS} = 15\text{ V}, T_c = 25^\circ\text{C}$	Fig. 22
Power Dissipation	$P_D$			341	W	$T_c = 25^\circ\text{C}, T_J = 175^\circ\text{C}$	Fig. 20
Operating Junction and Storage Temperature	$T_J, T_{stg}$			-55 to +175	$^\circ\text{C}$		
Solder Temperature	$T_L$			260		According to JEDEC J-STD-020	

Note (1): Recommended turn-on gate voltage is 15V with  $\pm 5\%$  regulation tolerance, see Application Note PRD-04814 for additional details

Note (2): Verified by design


**Electrical Characteristics** ( $T_c = 25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions	Note
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	1200			V	$V_{GS} = 0\text{ V}, I_D = 100\text{ }\mu\text{A}$	
$V_{GS(th)}$	Gate Threshold Voltage	1.8	2.9	3.8	V	$V_{DS} = V_{GS}, I_D = 10.7\text{ mA}$	Fig. 11
			2.4		V	$V_{DS} = V_{GS}, I_D = 10.7\text{ mA}, T_J = 175^\circ\text{C}$	
$I_{DSS}$	Zero Gate Voltage Drain Current		1	50	$\mu\text{A}$	$V_{DS} = 1200\text{ V}, V_{GS} = 0\text{ V}$	
$I_{GSS}$	Gate-Source Leakage Current		10	250	nA	$V_{GS} = 15\text{ V}, V_{DS} = 0\text{ V}$	
$R_{DS(on)}$	Drain-Source On-State Resistance		32	43	m $\Omega$	$V_{GS} = 15\text{ V}, I_D = 38.9\text{ A}$	Fig. 4, 5, 6
			55			$V_{GS} = 15\text{ V}, I_D = 38.9\text{ A}, T_J = 175^\circ\text{C}$	
$g_{fs}$	Transconductance		23		S	$V_{DS} = 20\text{ V}, I_{DS} = 38.9\text{ A}$	Fig. 7
			22			$V_{DS} = 20\text{ V}, I_{DS} = 38.9\text{ A}, T_J = 175^\circ\text{C}$	
$C_{iss}$	Input Capacitance		3460		pF	$V_{GS} = 0\text{ V}, V_{DS} = 0\text{ V to } 1000\text{ V}$ $f = 100\text{ kHz}$ $V_{AC} = 25\text{ mV}$	Fig. 17, 18
$C_{oss}$	Output Capacitance		126				
$C_{rss}$	Reverse Transfer Capacitance		7				
$E_{oss}$	$C_{oss}$ Stored Energy		71		$\mu\text{J}$	$V_{DS} = 1000\text{ V}, f = 100\text{ kHz}$	Fig. 16
$C_{o(er)}$	Effective Output Capacitance (Energy Related)		158		pF	$V_{GS} = 0\text{ V}, V_{DS} = 0\text{ to } 800\text{ V}$	Note: 3
$C_{o(tr)}$	Effective Output Capacitance (Time Related)		242		pF		
$E_{ON}$	Turn-On Switching Energy (Body Diode FWD)		657		$\mu\text{J}$	$V_{DS} = 800\text{ V}, V_{GS} = -4\text{ V}/15\text{ V}, I_D = 38.9\text{ A},$ $R_{G(ext)} = 2.5\text{ }\Omega, L = 99\text{ }\mu\text{H}, T_J = 175^\circ\text{C}$ FWD = Internal Body Diode	Fig. 26, 28
$E_{OFF}$	Turn-Off Switching Energy (Body Diode FWD)		67				
$t_{d(on)}$	Turn-On Delay Time		14		ns	$V_{DD} = 800\text{ V}, V_{GS} = -4\text{ V}/15\text{ V}, I_D = 38.9\text{ A},$ $R_{G(ext)} = 2.5\text{ }\Omega, L = 99\text{ }\mu\text{H}, T_J = 175^\circ\text{C}$ Timing relative to $V_{DS}$ Inductive load	Fig. 27, 28
$t_r$	Rise Time		19				
$t_{d(off)}$	Turn-Off Delay Time		25				
$t_f$	Fall Time		8				
$R_{G(int)}$	Internal Gate Resistance		1.1		$\Omega$	$f = 1\text{ MHz}, V_{AC} = 25\text{ mV}$	
$Q_{gs}$	Gate to Source Charge		41		nC	$V_{DS} = 800\text{ V}, V_{GS} = -4\text{ V}/15\text{ V}$ $I_D = 38.9\text{ A}$ Per IEC60747-8-4 pg 21	Fig. 12
$Q_{gd}$	Gate to Drain Charge		27				
$Q_g$	Total Gate Charge		108				

Note (3):  $C_{o(er)}$ , a lumped capacitance that gives same stored energy as  $C_{oss}$  while  $V_{ds}$  is rising from 0 to 800V

$C_{o(tr)}$ , a lumped capacitance that gives same charging time as  $C_{oss}$  while  $V_{ds}$  is rising from 0 to 800V


**Reverse Diode Characteristics** ( $T_c = 25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions	Note
$V_{SD}$	Diode Forward Voltage	4.9		V	$V_{GS} = -4\text{ V}, I_{SD} = 19.5\text{ A}, T_J = 25^\circ\text{C}$	Fig. 8, 9, 10
		4.3		V	$V_{GS} = -4\text{ V}, I_{SD} = 19.5\text{ A}, T_J = 175^\circ\text{C}$	
$I_S$	Continuous Diode Forward Current		58	A	$V_{GS} = -4\text{ V}, T_c = 25^\circ\text{C}$	
$I_{SM}$	Diode pulse Current		264	A	$V_{GS} = -4\text{ V}$ , pulse width $t_p$ limited by $T_{Jmax}$	
$t_{rr}$	Reverse Recover time	12		ns	$V_{GS} = -4\text{ V}, I_{SD} = 38.9\text{ A}, V_R = 800\text{ V}$ $di_F/dt = 8550\text{ A}/\mu\text{s}, T_J = 25^\circ\text{C}$	
$Q_{rr}$	Reverse Recovery Charge	367		nC		
$I_{rrm}$	Peak Reverse Recovery Current	56		A		
$t_{rr}$	Reverse Recover time	18		ns	$V_{GS} = -4\text{ V}, I_{SD} = 62.12\text{ A}, V_R = 800\text{ V}$ $di_F/dt = 2305\text{ A}/\mu\text{s}, T_J = 25^\circ\text{C}$	
$Q_{rr}$	Reverse Recovery Charge	191		nC		
$I_{rrm}$	Peak Reverse Recovery Current	19		A		

**Thermal Characteristics**

Symbol	Parameter	Typ.	Unit	Test Conditions	Note
$R_{\theta JC}$	Thermal Resistance from Junction to Case	0.34	$^\circ\text{C}/\text{W}$		Fig. 21



## Typical Performance




Figure 1. Output Characteristics  $T_J = -55\text{ }^{\circ}\text{C}$




Figure 2. Output Characteristics  $T_J = 25\text{ }^{\circ}\text{C}$




Figure 3. Output Characteristics  $T_J = 175\text{ }^{\circ}\text{C}$




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current  
For Various Temperatures




Figure 6. On-Resistance vs. Temperature  
For Various Gate Voltage

## Typical Performance




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic at -55 °C




Figure 9. Body Diode Characteristic at 25 °C




Figure 10. Body Diode Characteristic at 175 °C




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristics

## Typical Performance





Figure 13. 3rd Quadrant Characteristic at  $-55^{\circ}\text{C}$ Figure 14. 3rd Quadrant Characteristic at  $25^{\circ}\text{C}$ Figure 15. 3rd Quadrant Characteristic at  $175^{\circ}\text{C}$ 

Figure 16. Output Capacitor Stored Energy




Figure 17. Capacitances vs. Drain-Source Voltage (0 - 200V)




Figure 18. Capacitances vs. Drain-Source Voltage (0 - 1200V)

## Typical Performance




Figure 19. Continuous Drain Current Derating vs. Case Temperature




Figure 20. Maximum Power Dissipation Derating vs. Case Temperature




Figure 21. Transient Thermal Impedance (Junction - Case)




Figure 22. Safe Operating Area




Figure 23. Clamped Inductive Switching Energy vs. Drain Current ( $V_{DD} = 600V$ )




Figure 24. Clamped Inductive Switching Energy vs. Drain Current ( $V_{DD} = 800V$ )

## Typical Performance




Figure 25. Clamped Inductive Switching Energy vs.  $R_{G(\text{ext})}$




Figure 26. Clamped Inductive Switching Energy vs. Temperature




Figure 27. Switching Times vs.  $R_{G(\text{ext})}$




Figure 28. Switching Times Definition



## Test Circuit Schematic





Figure 29. Clamped Inductive Switching  
Waveform Test Circuit


Package Dimensions





**Recommended Solder Pad Layout**

All dimensions in mm



**Revision history**

Document Version	Date of release	Descriptiion of changes
1.0	February 2024	Initial release
2	December 2024	Legal Disclaimer Updated



## Notes & Disclaimer

---

WOLFSPEED PROVIDES TECHNICAL AND RELIABILITY DATA, DESIGN RESOURCES, APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, WITH RESPECT THERETO, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

This document and the information contained herein are subject to change without notice. Any such change shall be evidenced by the publication of an updated version of this document by Wolfsped. No communication from any employee or agent of Wolfsped or any third party shall effect an amendment or modification of this document. No responsibility is assumed by Wolfsped for any infringement of patents or other rights of third parties which may result from use of the information contained herein. No license is granted by implication or otherwise under any patent or patent rights of Wolfsped.

The information contained in this document (excluding examples, as well as figures or values that are labeled as “typical”) constitutes Wolfsped’s sole published specifications for the subject product. “Typical” parameters are the average values expected by Wolfsped in large quantities and are provided for informational purposes only. Any examples provided herein have not been produced under conditions intended to replicate any specific end use. Product performance can and does vary due to a number of factors.

This product has not been designed or tested for use in, and is not intended for use in, any application in which failure of the product would reasonably be expected to cause death, personal injury, or property damage. For purposes of (but without limiting) the foregoing, this product is not designed, intended, or authorized for use as a critical component in equipment implanted into the human body, life-support machines, cardiac defibrillators, and similar emergency medical equipment; air traffic control systems; or equipment used in the planning, construction, maintenance, or operation of nuclear facilities. Notwithstanding any application-specific information, guidance, assistance, or support that Wolfsped may provide, the buyer of this product is solely responsible for determining the suitability of this product for the buyer’s purposes, including without limitation (1) selecting the appropriate Wolfsped products for the buyer’s application, (2) designing, validating, and testing the buyer’s application, and (3) ensuring the buyer’s application meets applicable standards and any other legal, regulatory, and safety-related requirements.

### RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Wolfsped representative or from the Product Documentation sections of [www.wolfsped.com](http://www.wolfsped.com).

### REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact your Wolfsped representative to ensure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request. SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

### Contact info:

4600 Silicon Drive  
Durham, NC 27703 USA  
Tel: +1.919.313.5300  
[www.wolfsped.com/power](http://www.wolfsped.com/power)

© 2024 Wolfsped, Inc. All rights reserved. Wolfsped® and the Wolfstreak logo are registered trademarks and the Wolfsped logo is a trademark of Wolfsped, Inc.  
PATENT: <https://www.wolfsped.com/legal/patents>

*The information in this document is subject to change without notice.*