


C3M0120065L

Transition Guide

Wolfspeed  SEPTEMBER 2024

SUGGESTED REPLACEMENT

	C3M0120065L	C3M0060065L	Notes
Status	EOL issued Oct 2024	Active	200mm samples available now. Full release Q1 2025
$V_{DS\ max}$ (V)	650	650	
V_{GS} (V)	-4/+15	-4/+15	
I_D (A)	21	39	
$R_{DS(on)}$ (m Ω)	120	60	Significantly lower conduction losses
C_{oss} (pF)	45	72	
C_{iss}/C_{rss}	278	195	
Q_G (nC)	26	46	Increased gate drive power
$R_{G(int)}$ (Ω)	6	4	
$R_{\theta JC}$ (C/W)	1.38	0.89	Reduced thermal impedance
Package	TOLL	TOLL	Fully Compatible
Pricing			Similar Price

This replacement option is suitable for most designs and will result in improved performance for conduction loss dominated applications

All parameters are typical values at 25 °C unless noted

© 2024 Wolfspeed, Inc. All rights reserved. Wolfspeed® and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.

NEXT STEPS

- Samples of recommended replacements available through your [Wolfspeed sales team](#), or at our online [Sample Center](#)
- Ask any technical questions to your Wolfspeed FAE or through our [Power Applications Forum](#)
- Utilize [SpeedFit™](#) to simulate the performance of the recommended replacement devices
 - Keep in mind, dynamic behavior may be different, requiring a different gate resistor value
- The [SpeedVal™ Kit](#) evaluation platform may be utilized to compare the performance and switching behavior

A large, stylized grey graphic of a wolf's head is positioned in the background, facing right. The graphic is composed of several overlapping, angular shapes that define the snout, eye, and ear area. The text "THANK YOU" is centered over the middle of the wolf's snout.

THANK YOU