


CAB6R0A23GM4, CAB6R0A23GM4T

2300 V, 6.0 mΩ, Silicon Carbide, Half-Bridge Module

| | |
|--------------|---------------|
| V_{DS} | 2300 V |
| $R_{DS(on)}$ | 6.0 mΩ |

Technical Features

- Ultra-Low Loss, High Frequency Operation
- Zero Turn-Off Tail Current from MOSFET
- Normally-Off, Fail-Safe Device Operation
- Aluminium Nitride Substrate
- Optional Pre-Applied Thermal Interface Material
- Conforms to UL STD 1557



Typical Applications

- DC Fast Chargers
- Energy Storage Systems
- High-Efficiency Converters / Inverters
- Renewable Energy
- Smart-Grid / Grid-Tied Distributed Generation
- Solar Inverters

System Benefits

- Enables Compact, Lightweight Systems
- Enables Two-Level Conversion for 1500 VDC Systems
- Increased System Efficiency due to Low Switching & Conduction Losses of SiC
- Reduced Thermal Requirements and System Cost

Key Parameters

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Test Conditions | Note |
|---|---------------|------|-------|------|------------------|--|-------------------|
| Drain-Source Voltage | V_{DS} | | | 2300 | V | | |
| Maximum Gate-Source Voltage | $V_{GS(max)}$ | -10 | | +23 | | Transient | Fig. 33 |
| Operational Gate-Source Voltage | $V_{GS(op)}$ | | -4/15 | | | Static | Note 1 |
| DC Continuous Drain Current ($T_{VJ} \leq 150^\circ\text{C}$) | I_D | | | 150 | A | $V_{GS} = 15\text{ V}, T_{HS} = 75^\circ\text{C}, T_{VJ} \leq 150^\circ\text{C}$ | Notes 2,3,4 |
| Pulsed Drain Current | I_{DM} | | | 300 | | t_{Pmax} limited by T_{VJmax} $V_{GS} = 15\text{ V}, T_{HS} = 75^\circ\text{C}$ | Fig. 20 |
| Power Dissipation | P_D | | 610 | | W | $T_{HS} = 75^\circ\text{C}, T_{VJ} \leq 150^\circ\text{C}$ | Note 5 Fig. 21 |
| Virtual Junction Temperature | $T_{VJ(op)}$ | -40 | | 150 | $^\circ\text{C}$ | Operation | |

Note (1): Recommended turn-on gate voltage is 15 V with $\pm 5\%$ regulation tolerance

Note (2): Current limit at $T_{HS} = 75^\circ\text{C}, T_{VJ} \leq 150^\circ\text{C}$ imposed by package

Note (3): Continuous DC operational limit set by DC- pins. See Figure 22 for implementable AC current

Note (4): Verified by design

Note (5): $P_D = (T_{VJ} - T_{HS})/R_{TH(JH,typ)}$

MOSFET Characteristics (Per Position) ($T_{VJ} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Test Conditions | Note |
|--|---------------|------|-------------------|------|-----------------------------|---|--------------------|
| Drain-Source Breakdown Voltage | $V_{(BR)DSS}$ | 2300 | | | | $V_{GS} = 0\text{ V}$, $T_{VJ} = -40\text{ }^{\circ}\text{C}$ | |
| Gate Threshold Voltage | $V_{GS(th)}$ | 1.8 | 2.5 | 4.0 | V | $V_{DS} = V_{GS}$, $I_D = 95\text{ mA}$ | |
| | | | 2.1 | | | $V_{DS} = V_{GS}$, $I_D = 95\text{ mA}$, $T_{VJ} = 150\text{ }^{\circ}\text{C}$ | |
| Zero Gate Voltage Drain Current | I_{DSS} | | 13 | 750 | μA | $V_{GS} = 0\text{ V}$, $V_{DS} = 2300\text{ V}$ | |
| Gate-Source Leakage Current | I_{GSS} | | 63 | 1250 | nA | $V_{GS} = 15\text{ V}$, $V_{DS} = 0\text{ V}$ | |
| Drain-Source On-State Resistance (Devices Only) | $R_{DS(on)}$ | | 6.0 | 8.4 | m Ω | $V_{GS} = 15\text{ V}$, $I_D = 200\text{ A}$ | Fig. 2 Fig. 3 |
| | | | 14.3 | | | $V_{GS} = 15\text{ V}$, $I_D = 200\text{ A}$, $T_{VJ} = 150\text{ }^{\circ}\text{C}$ | |
| Transconductance | g_{fs} | | 210 | | S | $V_{DS} = 20\text{ V}$, $I_D = 200\text{ A}$ | Fig. 4 |
| | | | 205 | | | $V_{DS} = 20\text{ V}$, $I_D = 200\text{ A}$, $T_{VJ} = 150\text{ }^{\circ}\text{C}$ | |
| Turn-On Switching Energy, $T_{VJ} = 25\text{ }^{\circ}\text{C}$ $T_{VJ} = 125\text{ }^{\circ}\text{C}$ $T_{VJ} = 150\text{ }^{\circ}\text{C}$ | E_{On} | | 3.6 4.0 4.1 | | mJ | $V_{DD} = 1200\text{ V}$, $I_D = 200\text{ A}$, $V_{GS} = -4\text{ V}/15\text{ V}$, $R_{G(OFF)} = 0.0\text{ }\Omega$, $R_{G(ON)} = 0.0\text{ }\Omega$, $L_{\sigma} = 18\text{ nH}$ | Fig. 11 Fig. 13 |
| Turn-Off Switching Energy, $T_{VJ} = 25\text{ }^{\circ}\text{C}$ $T_{VJ} = 125\text{ }^{\circ}\text{C}$ $T_{VJ} = 150\text{ }^{\circ}\text{C}$ | E_{Off} | | 3.3 3.6 3.7 | | | | |
| Internal Gate Resistance | $R_{G(int)}$ | | 1.3 | | Ω | $f = 100\text{ kHz}$ | |
| Input Capacitance | C_{iss} | | 30.5 | | nF | $V_{GS} = 0\text{ V}$, $V_{DS} = 1500\text{ V}$, $V_{AC} = 25\text{ mV}$, $f = 100\text{ kHz}$ | Fig. 9 |
| Output Capacitance | C_{oss} | | 0.50 | | | | |
| Reverse Transfer Capacitance | C_{rss} | | 40 | | pF | | |
| Gate to Source Charge | Q_{GS} | | 230 | | nC | $V_{DS} = 1500\text{ V}$, $V_{GS} = -4\text{ V}/15\text{ V}$, $I_D = 200\text{ A}$, Per IEC60747-8-4 pg 21 | |
| Gate to Drain Charge | Q_{GD} | | 195 | | | | |
| Total Gate Charge | Q_G | | 735 | | | | |
| FET Thermal Resistance, Junction to Heatsink | $R_{th\ JHS}$ | | 0.121 | | $^{\circ}\text{C}/\text{W}$ | Measured with Pre-Applied TIM | Fig. 17 |

Diode Characteristics (Per Position) ($T_{VJ} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Test Conditions | Notes |
|--|--------------|------|-------------------|------|---------------|--|-------------------|
| Body Diode Forward Voltage | V_{SD} | | 5.8 | | V | $V_{GS} = -4\text{ V}$, $I_{SD} = 200\text{ A}$ | Fig. 7 |
| | | | 5.3 | | | $V_{GS} = -4\text{ V}$, $I_{SD} = 200\text{ A}$, $T_{VJ} = 150\text{ }^{\circ}\text{C}$ | |
| DC Source-Drain Current (Body Diode) | $I_{SD\ BD}$ | | 110 | | A | $V_{GS} = -4\text{ V}$, $T_{HS} = 75\text{ }^{\circ}\text{C}$, $T_{VJ} \leq 150\text{ }^{\circ}\text{C}$ | Note 5 Fig. 20 |
| Reverse Recovery Time | t_{RR} | | 390 | | ns | $V_{GS} = -4\text{ V}$, $I_{SD} = 200\text{ A}$, $V_R = 1200\text{ V}$ $di/dt = 19\text{ A/ns}$, $T_{VJ} = 150\text{ }^{\circ}\text{C}$ | Fig. 32 |
| Reverse Recovery Charge | Q_{RR} | | 10.5 | | μC | | |
| Peak Reverse Recovery Current | I_{RRM} | | 265 | | A | | |
| Reverse Recovery Energy, $T_{VJ} = 25\text{ }^{\circ}\text{C}$ $T_{VJ} = 125\text{ }^{\circ}\text{C}$ $T_{VJ} = 150\text{ }^{\circ}\text{C}$ | E_{RR} | | 1.7 6.0 8.8 | | mJ | $V_{DD} = 1200\text{ V}$, $I_D = 200\text{ A}$, $V_{GS} = -4\text{ V}/15\text{ V}$, $R_{G(ON)} = 0.0\text{ }\Omega$, $L_{\sigma} = 18\text{ nH}$ | Fig. 14 |



Module Physical Characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Test Conditions |
|------------------------------------|-------------|------|------|------|------------------|--|
| Package Resistance, M1 (High-Side) | R_{pkg1} | | 1.5 | | mΩ | $T_c = 125^\circ\text{C}$, Note 6 |
| Package Resistance, M2 (Low-Side) | R_{pkg2} | | 1.4 | | | |
| Stray Inductance | L_{stray} | | 11 | | nH | Between DC- and DC+, $f = 10\text{ MHz}$ |
| Case Temperature | T_c | -40 | | 125 | $^\circ\text{C}$ | |
| Mounting Torque | M_s | | 2.0 | 2.3 | N-m | M4 bolts |
| Weight | W | | 36 | | g | |
| Case Isolation Voltage | V_{isol} | 5 | | | kV | AC, 50 Hz, 1 minute |
| Comparative Tracking Index | CTI | 600 | | | | |
| Clearance Distance | | | 8.1 | | mm | Terminal to Terminal |
| | | | 13.2 | | | Terminal to Heatsink |
| Creepage Distance | | | 9.8 | | | Terminal to Terminal |
| | | | 14.9 | | | Terminal to Heatsink |

Note (6): Total Effective Resistance (Per Switch Position) = MOSFET $R_{DS(on)}$ + Switch Position Package Resistance

Temperature Sensor (NTC) Characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Test Conditions |
|--|------------------|------|------|------|------|------------------------------|
| Rated Resistance | R_{NTC} | | 5.0 | | kΩ | $T_{NTC} = 25^\circ\text{C}$ |
| Resistance Tolerance at 25 °C | $\Delta R/R$ | -5 | | 5 | % | |
| Beta Value ($T_2 = 50^\circ\text{C}$) | $\beta_{25/50}$ | | 3380 | | K | |
| Beta Value ($T_2 = 80^\circ\text{C}$) | $\beta_{25/80}$ | | 3468 | | K | |
| Beta Value ($T_2 = 100^\circ\text{C}$) | $\beta_{25/100}$ | | 3523 | | K | |
| Power Dissipation | P_{Max} | | | 10 | mW | $T_{NTC} = 25^\circ\text{C}$ |



Typical Performance




Figure 1. Output Characteristics for Various Junction Temperatures




Figure 2. Normalized On-State Resistance vs. Drain Current for Various Junction Temperatures




Figure 3. Normalized On-State Resistance vs. Junction Temperature




Figure 4. Transfer Characteristic for Various Junction Temperatures




Figure 5. 3rd Quadrant Characteristic vs. Junction Temperatures at $V_{GS} = 15\text{ V}$




Figure 6. 3rd Quadrant Characteristic vs. Junction Temperatures at $V_{GS} = 0\text{ V}$ (Body Diode)



Typical Performance




Figure 7. 3rd Quadrant Characteristic vs. Junction Temperatures at $V_{GS} = -4$ V (Body Diode)




Figure 8. Typical Capacitances vs. Drain to Source Voltage (0 - 200V)




Figure 9. Typical Capacitances vs. Drain to Source Voltage (0 - 2300V)




Figure 10. Threshold Voltage vs. Junction Temperature




Figure 11. Switching Energy vs. Drain Current ($V_{DD} = 1200$ V)




Figure 12. Switching Energy vs. Drain Current ($V_{DD} = 1500$ V)



Typical Performance




Figure 13. MOSFET Switching Energy vs. Junction Temperature




Figure 14. Reverse Recovery Energy vs. Junction Temperature




Figure 15. MOSFET Switching Energy vs. External Gate Resistance




Figure 16. Reverse Recovery Energy vs. External Gate Resistance




Figure 17. MOSFET Junction to Heatsink Transient Thermal Impedance, $Z_{th\ JHS}$ (°C/W)




Figure 18. Forward Bias Safe Operating Area (FBSOA)



Typical Performance




Figure 19. Switching Safe Operating Area




Figure 20. Continuous Drain Current Derating vs. Heatsink Temperature




Figure 21. Maximum Power Dissipation Derating vs. Heatsink Temperature




Figure 22. Typical Output Current Capability vs. Switching Frequency (Inverter Application)




Figure 23. Nominal NTC Resistance vs. NTC Temperature



Timing Characteristics




Figure 24. Timing vs. Source Current




Figure 25. dv/dt and di/dt vs. Source Current




Figure 26. Timing vs. Junction Temperature




Figure 27. dv/dt and di/dt vs. Junction Temperature




Figure 28. Timing vs. External Gate Resistance




Figure 29. dv/dt and di/dt vs. External Gate Resistance



Definitions




Figure 30. Turn-off Transient Definitions




Figure 31. Turn-on Transient Definitions




Figure 32. Reverse Recovery Definitions






Figure 33. V_{GS} Transient Definitions


Note (7): A gate driver featuring the IXDD614SI gate driver IC was used to evaluate dynamic performance. The typical driver high-state output resistance of 0.4 Ω and low-state output resistance of 0.3 Ω are not included in the RG(ext) values on this datasheet.



Schematic and Pin Out



Package Dimension (mm)



| DIMENSION TABLE | | |
|-------------------|-----------|---|
| SYMBOL | DIMENSION | TOLERANCE |
| A1 | 56.7 | ±0.30 |
| A2 | 62.8 | ±0.50 |
| A3 | 51 | ±0.15 |
| A4 | (53) | REF. |
| A5 | 22.7 | ±0.30 |
| A6 | 48 | ±0.30 |
| A7 | 42.5 | ±0.15 |
| A8 | 16.4 | ±0.20 |
| A9 | 4.5 | ±0.10 |
| A10 | ∅2.3 √8.5 | ∅: ⁺⁰ _{-0.10} √: ±0.30 |
| B1 | 16.4 | ±0.50 |
| B2 | 12.33 | ±0.35 |
| B4 | 1.8 | ±0.20 |
| ALL PIN LOCATIONS | | ±0.40 |



Product Ordering Code

| Part Number | Description |
|---------------|---|
| CAB6R0A23GM4 | Without Pre-Applied Phase Change Thermal Interface Material |
| CAB6R0A23GM4T | With Pre-Applied Phase Change Thermal Interface Material |

Supporting Links & Tools

Simulation Tools & Support

- [All LTSpice Models](#)
- [All PLECS Models](#)
- [SpeedFit 2.0 Design Simulator™](#)
- [Technical Support Forum](#)

Compatible Evaluation Hardware

- [EVAL-ADUM4146WHB1Z: Analog Devices® Gate Driver Board](#)
- [UCC21710QDWEVM-054: Texas Instruments® Gate Driver Board](#)
- [CGD1700HB2M-UNA: Wolfspeed Gate Driver Board](#)
- [CGD12HB00D: Differential Transceiver Daughter Board Companion Tool for Differential Gate Drivers](#)

Application Notes

- [PRD-02302: Wolfpack Mounting Instructions and PCB Requirements](#)
- [PRD-06379: Environmental Considerations for Power Electronics](#)
- [PRD-07845: Power Module Baseplate Capacitance and Electromagnetic Compatibility](#)
- [PRD-07933: Wolfspeed Power Module Thermal Interface Material Application User Guide](#)
- [PRD-07968: Wolfspeed WolfPACK™ Dynamic Performance](#)
- [PRD-08376: Thermal Characterization Methods and Applications](#)
- [PRD-08710: Measuring Stray Inductance in Power Electronics Systems](#)



Notes & Disclaimers

WOLFSPEED PROVIDES TECHNICAL AND RELIABILITY DATA, DESIGN RESOURCES, APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, WITH RESPECT THERETO, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

This document and the information contained herein are subject to change without notice. Any such change shall be evidenced by the publication of an updated version of this document by Wolfspeed. No communication from any employee or agent of Wolfspeed or any third party shall effect an amendment or modification of this document. No responsibility is assumed by Wolfspeed for any infringement of patents or other rights of third parties which may result from use of the information contained herein. No license is granted by implication or otherwise under any patent or patent rights of Wolfspeed.

The information contained in this document (excluding examples, as well as figures or values that are labeled as “typical”) constitutes Wolfspeed’s sole published specifications for the subject product. “Typical” parameters are the average values expected by Wolfspeed in large quantities and are provided for informational purposes only. Any examples provided herein have not been produced under conditions intended to replicate any specific end use. Product performance can and does vary due to a number of factors.

This product has not been designed or tested for use in, and is not intended for use in, any application in which failure of the product would reasonably be expected to cause death, personal injury, or property damage. For purposes of (but without limiting) the foregoing, this product is not designed, intended, or authorized for use as a critical component in equipment implanted into the human body, life-support machines, cardiac defibrillators, and similar emergency medical equipment; air traffic control systems; or equipment used in the planning, construction, maintenance, or operation of nuclear facilities. Notwithstanding any application-specific information, guidance, assistance, or support that Wolfspeed may provide, the buyer of this product is solely responsible for determining the suitability of this product for the buyer’s purposes, including without limitation (1) selecting the appropriate Wolfspeed products for the buyer’s application, (2) designing, validating, and testing the buyer’s application, and (3) ensuring the buyer’s application meets applicable standards and any other legal, regulatory, and safety-related requirements.

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Wolfspeed representative or from the Product Documentation sections of www.wolfspeed.com.

REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact your Wolfspeed representative to ensure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

Contact info:

4600 Silicon Drive
Durham, NC 27703 USA
Tel: +1.919.313.5300
www.wolfspeed.com/power